

Model MGP 8000

- Engine powered by HONDA
- Power up to 6,43 kW
- Easy to transport
- 11,8 h of autonomy



image example purpose only

MODEL CODE		MGP 8000 PE612SHI00A	
EROGATION SYSTEM		Single-phase	
POWER COP	kW	6,00	
Power LTP	kW	7,11	
Voltage	Volt	230	
Frequency	Hz	50	
Factor power	Cos φ	0,9	
ENGINE			
Model		HONDA GX390	
Displacement	cc	389	
Cylinder		1 inclination angle	
Starting System		Recoil	
Power Max	kW	7,7	
Fuel		unleaded petrol	
TANK / AUTONOMY			
Tank Capacity	L	25,7	
Autonomy 75%	h	11,8	
NOISE LEVEL			
Noise Level LWA	dB(A)	97	
Acoustic pressure at 7 m	dB(A)	71,5	
DIMENSIONS			
Lenght	mm	725	
Width	mm	503	
Height	mm	535	
Weight	kg	78	

TECHNICAL FEATURES

THE PRODUCER RESERVES THE RIGHT TO INTRODUCE CHANGES TO MODELS AND FEATURES WITHOUT PRIOR NOTICES.

MANUAL PANEL			
	Protections	Oil-guard Thermal protection IP23 Electric IP 44 Socket	
	Controls	On Off Lever / Choke Lever / Fuel Gauge	
	Outputs	N.1 SCHUKO 230V 16A and N.1 CEE 230V 32A (UK version code PE612SHI008 with 1 CEE 115V 32A and 1 CEE 230V 32A)	
	Options	Transportation kit	

