

GS PRO Series

Making the load tigher

Hand pallet trucks

GS Basic Series

GS PRO Series

GS Special Series

GS Premium Series

GS Mister Hydro Series

GS 30 Series

- Scale trucks
- High-lift pallet trucks
- Electric pallet trucks
- Manual stackers
- Semi-electric stackers
- Electric stackers
- Counterbalanced trucks

Spare parts and additional services

Discover our online services to buy spare parts and additional services:

- Buy spare parts online
- Scheduled maintenance services
- Technical support

Lifter GS/RA 25S2 1150x525

Item code: GF541A0F100



(purely indicative picture)

Main features

Nominal load capacity : **2500 kg**
 Frame material : **Painted steel**
 Fork length : **1150 mm**
 Fork width : **150 mm**
 Stowage passage : **1832 mm**
 Turning radius : **1367 mm**

GS PRO Series

The GS Pro Series, is an excellent tool for lifting and carrying loads on pallets or size-standardised containers. Thanks to its light weight, smooth movement and manoeuvrability, all the GS Series models are an ideal working tool for use on smooth floors and other kinds of surfaces.

Technical specifications

Main specifications

Nominal load capacity	2500 kg
Load center distance	575 mm
Propelling system	Manual
Driving system	Pedestrian
Lifting system	Manual
Frame material	Painted steel
Compliance certification	CE

Performances

Operating brake	n.a.
Parking brake	Optional
Lifting speed, without load	13 strokes
Lifting speed, with load	13 strokes
Lowering speed, without load	0,05 m/s
Lowering speed, with load	0,1 m/s
Lowering speed, without load - second speed	n.a.
Lowering speed, with load - second speed	n.a.

Dimensional data

Lift height	200 mm
Normal free lifting	115 mm
Fork length	1150 mm
Fork width	150 mm
Forks thickness	55 mm
Lowered forks height	85 mm
Overall width	525 mm
Overall length	1550 mm
Overall height (handle)	1160 mm
Stowage passage	1832 mm
Turning radius	1367 mm
Drive unit length	400 mm
Frame, wheel base	1192 mm
Frame, load axle to end forks	215 mm

Wheels

Front wheels width	55 mm
Front wheels diameter	200 mm
Front wheels material	Poly - Nylon
Front track	145 mm
Rear wheels number	2
Rear wheels width	82 mm
Rear wheels diameter	82 mm

Rear wheels material	Nylon
Rear track	375 mm
Rear balancing axle	No
Other equipments	
Entry/exit system	Yes
Weights	
Weight without load	61 kg
Front axle load, without load	42 kg
Front axle load, with load	767 kg
Rear axle load, without load	19 kg
Rear axle load, with load	1794 kg
Additional information	
Operating conditions: minimum temperature	-12 °C
Operating conditions: maximum temperature	50 °C

Technical specifications are subject to change without notice. Consult your local Lifter representative for more information.